

View Online at <https://aerobasegroup.com/nsn/5930-01-369-9000>

**Thread Class:**

3a single pressure connection

**Thread Length:**

0.780 inches single pressure connection

**Overall Length:**

6.090 inches

**Outside Diameter:**

0.250 inches single connection

**Overall Height:**

4.720 inches

**Overall Width:**

4.120 inches

**Mounting Slot Width:**

0.250 inches

**Body Length:**

6.090 inches

**Body Height:**

3.940 inches

**Distance Between Mounting Facility Centers:**

0.250 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between 0.0 degrees fahrenheit and 150.0 degrees fahrenheit

**Mounting Method:**

Bracket and slot

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load fourth voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

0.00 actuation point pounds per square inch and 600.00 actuation point pounds per square inch and 0.00 deactuation point pounds per square inch and 600.00 deactuation point pounds per square inch

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A048b0