

View Online at <https://aerobasegroup.com/nsn/5930-01-370-0924>

Hazardous Locations/environmental Protection:

Shock proof and watertight

Overall Length:

3.520 inches

Overall Height:

1.740 inches

Overall Width:

2.120 inches

Unthreaded Mounting Hole Diameter:

0.189 inches single mounting facility

Individual Section Quantity:

1

Knob Specificational Markings:

Normal override alarm

Longest Horizontal Distance Between Mounting Centers:

1.620 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

End Application:

27192-6962ed3152 ac magnetic controller

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level115.0 lowest ac voltage rating at sea level355.0 highest dc voltage rating at sea level115.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Terminal Type:

Tab w/screw

Contact Load Current Rating:

7.5 amperes inductive load highest ac voltage rating at sea level30.0 amperes inductive load lowest ac voltage rating at sea level0.4 amperes inductive load highest dc voltage rating at sea level1.1 amperes inductive load lowest dc voltage rating at sea level

Test Data Document:

27192-6981ed200 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0