# NSN 5930-01-370-0925

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-370-0925

Thread Class.
Thread Class:
2a Pada Stalas
Body Style:
Bushing mount
Hazardous Locations/environmental Protection:
Vibration resistant and shock proof and corrosion proof and salt water resistant and moisture resistant and sand proof
Overall Length:
1.270 inches
Overall Height:
3.590 inches
Overall Width:
0.635 inches
Bushing Length:
0.470 inches
Body Length:
1.270 inches
Body Width:
0.635 inches
Actuator Style:
Round
Actuator Diameter:
0.420 inches
Actuator Height:
Between 1.050 inches and 1.140 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained
Actuator Position-locking Relationship:
Up position no locking action and down position locked in
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
1.980 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches

## NSN 5930-01-370-0925

Toggle Switch - Page 2 of 2



#### **Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

### **Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes lamp ac

#### **Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

orbas miles oboo specification (includes engineering type balletins, brotheres, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 turret
Specification Data:
96906-ms27737 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A053a0