

View Online at <https://aerobasegroup.com/nsn/5930-01-370-1871>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.880 inches

Body Length:

1.090 inches

Body Width:

0.400 inches

Body Height:

0.630 inches

Unthreaded Mounting Hole Diameter:

0.110 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.410 inches

Maximum Voltage Rating In Volts:

125.0 ac and 250.0 dc

End Application:

Emory s. Land class as, ticondaroga class c (47) , forrestral class cv, nimitz class cvn, mars class t-afs 1, tarawa class lha, oliver perry class ffg, arleigh burke class ddg, wasp class lhd

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes lamp ac and 250.0 milliamperes inductive dc

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0