## NSN 5930-01-370-1871

Sensitive Switch - Page 1 of 1

No Fiig: A053a0



View Online at https://aerobasegroup.com/nsn/5930-01-370-1871 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.880 inches **Body Length:** 1.090 inches **Body Width:** 0.400 inches **Body Height:** 0.630 inches **Unthreaded Mounting Hole Diameter:** 0.110 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.410 inches **Maximum Voltage Rating In Volts:** 125.0 ac and 250.0 dc **End Application:** Emory s. Land class as, ticondaroga class c (47), forrestral class cv, nimitz class cvn, mars class t-afs 1, tarawa class lha, oliver perry class ffg, arleigh burke class ddg, wasp class lhd **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Criticality Code Justification:** Feat **Contact Load Current Rating At Maximum Rated Voltage:** 3.000 amperes lamp ac and 250.0 milliamperes inductive dc **Special Features:** Weapon system essential **Terminal Type And Quantity:** 3 quick disconnect, male Shelf Life: N/a **Unit Of Measure: Demilitarization:**