

View Online at <https://aerobasegroup.com/nsn/5930-01-370-2329>

Thread Class:

2a single mounting facility

Thread Length:

0.417 inches single mounting facility and 0.457 inches single mounting facility

Overall Length:

2.326 inches

Overall Diameter:

Between 1.031 inches and 1.041 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Distance Between Mounting Facility Centers:

0.360 inches single mounting facility and 0.390 inches single mounting facility

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

6 each section front

Throw Quantity:

2 each section front

Mounting Method:

Threaded bushing single mounting facility

Pile-up Contact Form Arrangement:

E each switch each section in-line

Thread Size:

0.375 inches single mounting facility

Rotor Through Connection Quantity:

5 each section

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

2 all actuators

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Special Features:

This item has special contact plating. Also per note 3.1 and 3.2 of drawing this item is related to critical functions within a missile system.

Precious Material And Location:

On the contact surface gold and on the contact surface silver

Precious Material:

Gold and silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0