

View Online at <https://aerobasegroup.com/nsn/5930-01-370-5371>

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Longest Horizontal Distance Between Mounting Centers:

5.500 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

4.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level110.0 lowest ac voltage rating at sea level250.0 highest dc voltage rating at sea level115.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

35.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load highest ac voltage rating at sea level15.0 amperes resistive load lowest ac voltage rating at sea level15.0 amperes resistive load highest dc voltage rating at sea level15.0 amperes resistive load lowest dc voltage rating at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0