NSN 5930-01-370-5372Rotary Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-370-5372 |
|---|
| Thread Length: |
| 0.312 inches single mounting facility |
| Overall Length: |
| 1.679 inches |
| First Flat Length: |
| 0.250 inches single actuator |
| Flat Height: |
| 0.094 inches single actuator |
| Shaft Diameter: |
| 0.125 inches single actuator |
| Shaft Length: |
| 0.375 inches single actuator |
| Overall Diameter: |
| 0.800 inches |
| Individual Section Quantity: |
| 1 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Contact Voltage Rating In Volts: |
| 115.0 ac at sea level28.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 9 single actuator |
| Shaft Type: |
| Round, flatted single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 75.0 milliamperes resistive load ac at sea level125.0 milliamperes resistive load dc at sea level |
| Style Designator: |
| Tap, circular, bushing mount |
| Test Data Document: |
| 81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-s-3786/13 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 5930-01-370-5372Rotary Switch - Page 2 of 2



Fiig:

A052b0