NSN 5930-01-370-5372

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-370-5372

## **Thread Length:**

0.312 inches single mounting facility

## **Overall Length:**

1.679 inches

#### First Flat Length:

0.250 inches single actuator

## Flat Height:

0.094 inches single actuator

#### Shaft Diameter:

0.125 inches single actuator

#### Shaft Length:

0.375 inches single actuator

#### **Overall Diameter:**

0.800 inches

#### Individual Section Quantity:

1 Switch Contact Basic Design:

## .....

Nonpile-up symmetrical

## Mounting Method:

Threaded bushing single mounting facility

## **Contact Voltage Rating In Volts:**

115.0 ac at sea level28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

9 single actuator

Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Load Current Rating:**

75.0 milliamperes resistive load ac at sea level125.0 milliamperes resistive load dc at sea level

#### Style Designator:

Tap, circular, bushing mount

## Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-s-3786/13 government specification

### Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

# **NSN 5930-01-370-5372** Rotary Switch - Page 2 of 2

Fiig: A052b0

