

View Online at <https://aerobasegroup.com/nsn/5930-01-370-6419>

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -4.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:**

Bracket

**Proof Pressure:**

200.00 pounds per square inch gage

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Contact Load Current Rating:**

0.5 amperes resistive load first voltage0.25 amperes resistive load second voltage0.5 amperes resistive load third voltage0.5 amperes resistive load fourth voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+3.00/+100.00 actuation point pounds per square inch gage and +3.00/+100.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point hex nut and external deactuation point hex nut

**Contact Voltage Rating In Volts:**

125.0 dc at sea level first voltage250.0 dc at sea level second voltage125.0 ac at sea level third voltage250.0 ac at sea level fourth voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0