

View Online at <https://aerobasegroup.com/nsn/5930-01-370-6419>

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -4.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Bracket

Proof Pressure:

200.00 pounds per square inch gage

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Contact Load Current Rating:

0.5 amperes resistive load first voltage0.25 amperes resistive load second voltage0.5 amperes resistive load third voltage0.5 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+3.00/+100.00 actuation point pounds per square inch gage and +3.00/+100.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point hex nut and external deactuation point hex nut

Contact Voltage Rating In Volts:

125.0 dc at sea level first voltage250.0 dc at sea level second voltage125.0 ac at sea level third voltage250.0 ac at sea level fourth voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0