

View Online at <https://aerobasegroup.com/nsn/5930-01-370-9767>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight and shock resistant and vibration resistant

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.465 inches and 0.470 inches

**Actuator Height:**

0.590 inches

**Housing Height:**

2.280 inches

**Housing Length:**

4.940 inches

**Housing Width:**

2.280 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.623 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

2.250 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, both positions maintained single switch unit

**Switch Release Force:**

240.0 inch-ounces

**Switch Actuating Force:**

240.0 inch-ounces

**Actuator Movement:**

18.0 pretravel degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac and 1.500 amperes resistive dc

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0