

View Online at <https://aerobasegroup.com/nsn/5930-01-370-9767>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight and shock resistant and vibration resistant

Actuator Style:

Round

Actuator Diameter:

Between 0.465 inches and 0.470 inches

Actuator Height:

0.590 inches

Housing Height:

2.280 inches

Housing Length:

4.940 inches

Housing Width:

2.280 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.623 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.250 inches

Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Switch Release Force:

240.0 inch-ounces

Switch Actuating Force:

240.0 inch-ounces

Actuator Movement:

18.0 pretravel degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 1.500 amperes resistive dc

Precious Material And Location:

Contacts silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0