

View Online at <https://aerobasegroup.com/nsn/5930-01-371-2083>

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.810 inches

Body Width:

0.640 inches

Body Height:

1.130 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.145 inches

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 0.625 inches and 0.780 inches

Actuator Roller Diameter:

0.380 inches

Actuator Roller Width:

0.160 inches

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

4920ncd161986, cage k0656

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

18.0 ounces

Actuator Movement:

0.250 pretravel inches and 0.062 overtravel inches and 0.090 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0