

View Online at <https://aerobasegroup.com/nsn/5930-01-371-8108>

Thread Class:

2b

Body Style:

Hole mount

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.812 inches

Body Length:

2.250 inches

Body Width:

0.969 inches

Body Height:

1.375 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.750 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

24.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

22.000 amperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes lamp dc

Test Data Document:

96906-ms39061 standard (includes industry or association standards, individual manufactureer standards, etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Specification Data:

96906-ms39061-5 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0