

View Online at <https://aerobasegroup.com/nsn/5930-01-371-8815>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Driptight

**Body Width:**

0.960 inches

**Body Height:**

0.960 inches

**Actuator Length:**

0.490 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.960 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

2.364 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive ac and 4.000 amperes inductive ac and 7.500 amperes resistive dc and 4.000 amperes inductive dc and 1.000 amperes lamp dc

**Precious Material And Location:**

Contact surfaces gold and contacts silver

**Unable To Decode:**

Unable to decode and unable to decode

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

1 connector, plug

**Specification Data:**

81349-mil-s-22885/108 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0