

View Online at <https://aerobasegroup.com/nsn/5930-01-372-0233>

Inside Diameter:

0.250 inches single connection

Overall Length:

4.500 inches

Overall Height:

1.500 inches

Overall Width:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.209 inches

Distance Between Mounting Facility Centers:

1.120 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 180.0 degrees fahrenheit

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

7500.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load first voltage5.0 amperes resistive load second voltage5.0 amperes resistive load third voltage and 3.0 amperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+40.00/+3050.00 actuation point pounds per square inch gage and +20.00/+2800.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point screw

Contact Voltage Rating In Volts:

125.0 ac at sea level first voltage250.0 ac at sea level second voltage28.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0