

View Online at <https://aerobasegroup.com/nsn/5930-01-372-0233>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

4.500 inches

**Overall Height:**

1.500 inches

**Overall Width:**

1.500 inches

**Unthreaded Mounting Hole Diameter:**

0.209 inches

**Distance Between Mounting Facility Centers:**

1.120 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -40.0 degrees fahrenheit and 180.0 degrees fahrenheit

**Mounting Method:**

Unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

7500.00 pounds per square inch gage

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage 5.0 amperes resistive load second voltage 5.0 amperes resistive load third voltage and 3.0 amperes inductive load third voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+40.00/+3050.00 actuation point pounds per square inch gage and +20.00/+2800.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal actuation point screw

**Contact Voltage Rating In Volts:**

125.0 ac at sea level first voltage 250.0 ac at sea level second voltage 28.0 dc at sea level third voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 first voltage60.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0