

View Online at <https://aerobasegroup.com/nsn/5930-01-372-0238>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Body Diameter:**

0.750 inches

**Bushing Length:**

0.469 inches

**Body Length:**

1.481 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.310 inches

**Actuator Free Position Height:**

0.310 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

32.0 ounces

**Switch Actuating Force:**

Between 40.0 ounces and 160.0 ounces

**Actuator Movement:**

0.040 pretravel inches and 0.125 overtravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0