

View Online at <https://aerobasegroup.com/nsn/5930-01-372-5384>

Overall Length:

2.796 inches

First Flat Length:

0.512 inches single actuator

Flat Height:

0.173 inches single actuator

Shaft Diameter:

0.236 inches single actuator

Shaft Length:

0.591 inches single actuator

Overall Diameter:

2.992 inches

Unthreaded Mounting Hole Diameter:

0.177 inches single mounting facility

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

11 single section front

Mounting Facility Circle Radius:

0.787 inches single mounting facility

Mounting Method:

Threaded bushing single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Shaft Flat/slot Angular Location:

15.0 degrees from nonturn device single actuator

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

11 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0