

View Online at <https://aerobasegroup.com/nsn/5930-01-372-8084>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Water resistant and oil resistant and corrosion resistant

**Body Diameter:**

1.015 inches

**Bushing Length:**

Between 0.970 inches and 1.030 inches

**Body Length:**

0.980 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.375 inches

**Actuator Free Position Height:**

1.375 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Mk32 mod17 tu e/i fscm39650

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally closed, momentary action single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 72.0 ounces and 144.0 ounces

**Actuator Movement:**

Between 0.070 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes inductive dc and 4.000 amperes motor dc and 4.000 amperes resistive dc

**Special Features:**

Altered item - make from ms24331-1

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 wire lead and 3 solderless lug and 1 crimp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0