## NSN 5930-01-373-5000

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-373-5000 **Overall Length:** 5.240 inches **Overall Height:** 5.520 inches **Overall Width:** 2.680 inches **Body Length:** 5.240 inches **Body Height:** 2.740 inches **Unthreaded Mounting Hole Diameter:** Between 0.276 inches and 0.286 inches **Distance Between Mounting Facility Centers:** 5.240 inches Capillary Tube Length: 180.000 inches **Longest Horizontal Distance Between Mounting Centers:** 1.380 inches **Shortest Horizontal Distance Between Mounting Centers:** 1.380 inches **Intermediate Horizontal Distance Between Mounting Centers:** 1.380 inches **Longest Vertical Distance Between Mounting Centers:** 5.240 inches **Shortest Vertical Distance Between Mounting Centers:** 5.180 inches **Tempurature Sensing Element Type:** Capillary tube **Operating Tempurature Rating:** 130.000 degrees celsius **Mounting Method:** Flange and unthreaded hole **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 2 two circuit, double break/double make, both positions maintained **Terminal Type:** 

Wire lead

**Contact Adjustability:** 

Actuation point adjustable, preset

## NSN 5930-01-373-5000

Thermostatic Switch - Page 2 of 2



Contact Adjustment Range:
+90.00/+165.00 actuation point dynes per square centimeter
Contact Adjustment Type:
Internal actuation point screw
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No **Fiig:** 

A048b0