

View Online at <https://aerobasegroup.com/nsn/5930-01-373-6381>

Overall Length:

5.240 inches

Overall Height:

2.460 inches

Mounting Slot Width:

0.220 inches

Body Length:

3.830 inches

Body Width:

2.060 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and slot

Contact Action Stimulus:

Decrease

Proof Pressure:

475.00 pounds per square inch

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

6.0 amperes inductive load first voltage1.2 amperes inductive load second voltage220.0 milliamperes inductive load third voltage110.0 milliamperes inductive load fourth voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+3.00/+150.00 actuation point pounds per square inch and +5.00/+169.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point dial and external deactuation point dial

Contact Voltage Rating In Volts:

120.0 ac at sea level first voltage600.0 ac at sea level second voltage125.0 dc at sea level third voltage250.0 dc at sea level fourth voltage

Pressure Connector Type:

Flared, threaded external single connection

Frequency In Hertz:

60.0 first voltage60.0 second voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0