

View Online at <https://aerobasegroup.com/nsn/5930-01-373-6386>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.220 inches

Actuator Length:

1.560 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

2.220 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.310 inches

Housing Height:

1.800 inches

Housing Length:

3.900 inches

Housing Width:

1.020 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.220 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.950 inches

Maximum Voltage Rating In Volts:

250.0 dc and 600.0 ac

End Application:

6640-00-902-9711

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.000 ounces

Switch Actuating Force:

Between 10.0 ounces and 20.0 ounces

Actuator Movement:

Between 0.188 pretravel inches and 0.219 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.250 amperes resistive dc and 2.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0