

View Online at <https://aerobasegroup.com/nsn/5930-01-373-6386>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Weatherproof

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.220 inches

**Actuator Length:**

1.560 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

2.220 inches

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.310 inches

**Housing Height:**

1.800 inches

**Housing Length:**

3.900 inches

**Housing Width:**

1.020 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

1.220 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.950 inches

**Maximum Voltage Rating In Volts:**

250.0 dc and 600.0 ac

**End Application:**

6640-00-902-9711

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.000 ounces

**Switch Actuating Force:**

Between 10.0 ounces and 20.0 ounces

**Actuator Movement:**

Between 0.188 pretravel inches and 0.219 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

0.250 amperes resistive dc and 2.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0