

View Online at <https://aerobasegroup.com/nsn/5930-01-373-9824>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

Between 1.242 inches and 1.342 inches

**Overall Diameter:**

Between 0.485 inches and 0.515 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level 28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

150.0 milliamperes resistive load ac at sea level 30.0 milliamperes inductive load dc at sea level and 100.0 milliamperes lamp load dc at sea level and 200.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Terminals, contacts and rotor surfaces gold and terminals, contacts, and rotor surfaces silver

**Precious Material:**

Gold and silver

**Style Designator:**

Miniature, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0