

View Online at <https://aerobasegroup.com/nsn/5930-01-375-6651>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Driptight

Body Width:

0.750 inches

Body Height:

0.750 inches

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.180 inches

Actuator Width:

0.620 inches

Illuminated Actuator Color:

Green single actuator and yellow single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

Between 1.160 inches and 1.500 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.0 milliamperes inductive dc

Precious Material And Location:

Contacts gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 tab, solder lug

Specification Data:

81349-mil-s-22885/101 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0