NSN 5930-01-376-7619

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-376-7619
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Vibration resistant
Body Width:
0.750 inches
Body Height:
1.000 inches
Actuator Length:
0.680 inches
Actuator Style:
Rectangular
Actuator Height:
0.250 inches
Actuator Width:
0.430 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green single actuator and red single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator red lower half of actuator green
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.472 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens and mounting hardware
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac and 3.000 amperes resistive dc and 1.5000
amperes inductive dc and 1.500 amperes lamp dc
Special Features:
Switch shall mount in any panel with a thickness of 0.190 porm 0.020
Terminal Type And Quantity:

Shelf Life: N/a

15 tab, solder lug

NSN 5930-01-376-7619

Push Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0