

View Online at <https://aerobasegroup.com/nsn/5930-01-376-7619>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Vibration resistant

Body Width:

0.750 inches

Body Height:

1.000 inches

Actuator Length:

0.680 inches

Actuator Style:

Rectangular

Actuator Height:

0.250 inches

Actuator Width:

0.430 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Green single actuator and red single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator red lower half of actuator green

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.472 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Horizontal split lens and mounting hardware

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac and 3.000 amperes resistive dc and 1.5000 amperes inductive dc and 1.500 amperes lamp dc

Special Features:

Switch shall mount in any panel with a thickness of 0.190 porm 0.020

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0