

View Online at <https://aerobasegroup.com/nsn/5930-01-377-0135>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Driptight

Body Width:

0.960 inches

Body Height:

0.960 inches

Actuator Length:

0.490 inches

Actuator Style:

Rectangular

Actuator Width:

0.490 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.654 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and full display lens

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive ac and 4.000 amperes inductive ac and 7.000 amperes resistive dc

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 connector, plug

Specification Data:

81349-mil-s-22885/108 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0