

View Online at <https://aerobasegroup.com/nsn/5930-01-379-0109>

**Thread Length:**

0.551 inches single mounting facility

**Overall Length:**

2.504 inches

**First Flat Length:**

0.512 inches single actuator

**Flat Height:**

0.173 inches single actuator

**Shaft Diameter:**

0.236 inches single actuator

**Shaft Length:**

0.614 inches single actuator

**Overall Diameter:**

1.732 inches

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Slotted bushing at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

11 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

10.0 millimeters single mounting facility

**Contact Voltage Rating In Volts:**

250.0 highest ac voltage rating at altitude

**Thread Pitch In Millimeters:**

0.75 single mounting facility

**Rotor Through Connection Quantity:**

1 single section

**Switch Actuator Indexing Position Quantity:**

11 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

6.0 amperes resistive load lowest ac voltage rating at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Iso s single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0