

View Online at <https://aerobasegroup.com/nsn/5930-01-379-0109>

Thread Length:

0.551 inches single mounting facility

Overall Length:

2.504 inches

First Flat Length:

0.512 inches single actuator

Flat Height:

0.173 inches single actuator

Shaft Diameter:

0.236 inches single actuator

Shaft Length:

0.614 inches single actuator

Overall Diameter:

1.732 inches

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

11 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

10.0 millimeters single mounting facility

Contact Voltage Rating In Volts:

250.0 highest ac voltage rating at altitude

Thread Pitch In Millimeters:

0.75 single mounting facility

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

11 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

6.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Iso s single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0