NSN 5930-01-382-6296

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-382-6296

Thread Class:

3a single pressure connection

Overall Length:

96.6 millimeters

Outside Diameter:

0.437 inches single connection

End Application:

Mk75 gun mount (cage 53711)

Pressure Switch Type:

Gage

Width Across Flats:

25.4 millimeters

Operating Tempurature Rating:

Between -18.0 degrees celsius and 82.0 degrees celsius

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

316.40 kilograms per square centimeter

Thread Size:

0.437 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point not adjustable

Contact Stimulus Rating:

56.00 actuation point kilograms per square centimeter and 9.00 deactuation point kilograms per square centimeter

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Compression, threaded external single connection

Special Features:

Six 1.2mm holes in hex for lock wire

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

NSN 5930-01-382-6296

Pressure Switch - Page 2 of 2



T	'nr	ead	Series	Design	nator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0