

View Online at <https://aerobasegroup.com/nsn/5930-01-384-9552>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

Between 0.395 inches and 0.425 inches

Body Length:

0.500 inches

Body Width:

Between 0.640 inches and 0.660 inches

Body Height:

Between 0.467 inches and 0.483 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.112 inches and 0.118 inches

Actuator Height:

Between 0.395 inches and 0.425 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive ac and 2.000 amperes resistive dc

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0