

View Online at <https://aerobasegroup.com/nsn/5930-01-388-0851>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Watertight

**Body Diameter:**

0.380 inches

**Body Length:**

0.535 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.190 inches

**Actuator Height:**

0.110 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

1 pole, single throw, double make, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac and 3.000 amperes inductive ac and 1.000 amperes lamp ac and 3.000 amperes motor ac and 5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes motor dc

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Data:**

81349-mil-s-8805/110 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0