

View Online at <https://aerobasegroup.com/nsn/5930-01-389-3743>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Driptight

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.160 inches and 0.270 inches

**Actuator Width:**

0.750 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Amber single actuator and red single actuator

**Actuator Inscription:**

Power/error single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Support equipment, aircraft f-16

**Mounting Surface To Terminal End Distance:**

1.390 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Three-way split lens

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

Switch shall be emi/rfi shielded as specified in mil-s-22885

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

16 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0