

View Online at <https://aerobasegroup.com/nsn/5930-01-389-3743>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Driptight

Body Width:

0.750 inches

Body Height:

0.750 inches

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.160 inches and 0.270 inches

Actuator Width:

0.750 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Amber single actuator and red single actuator

Actuator Inscription:

Power/error single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Support equipment, aircraft f-16

Mounting Surface To Terminal End Distance:

1.390 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Three-way split lens

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Switch shall be emi/rfi shielded as specified in mil-s-22885

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0