

View Online at <https://aerobasegroup.com/nsn/5930-01-391-2424>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.470 inches

Body Length:

1.100 inches

Body Width:

0.670 inches

Body Height:

1.150 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Base and press fit and sweated

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 7.000 amperes resistive ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 turret

Specification Data:

81349-mil-s-8805/98 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0