

View Online at <https://aerobasegroup.com/nsn/5930-01-391-6216>

Thread Class:

2a

Body Style:

Printed circuit

Body Length:

Between 0.515 inches and 0.531 inches

Body Width:

Between 0.267 inches and 0.283 inches

Body Height:

Between 0.315 inches and 0.393 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

Between 0.505 inches and 0.535 inches

Actuator Width:

Between 0.092 inches and 0.108 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position no locking action

Actuator Color:

Silver single actuator

Maximum Voltage Rating In Volts:

120.0 ac or 250.0 ac

End Application:

Hu-25 coast guard aircraft

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Mounting hardware

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes inductive ac and 2.000 amperes inductive ac

Special Features:

One locking ring 1/4 inch, one lock washer 1/4 inch, 2 nuts 1/4 inch-40 ns 2b

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0