

View Online at <https://aerobasegroup.com/nsn/5930-01-392-0608>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Vaportight

Overall Length:

1.270 inches

Bushing Length:

Between 0.455 inches and 0.485 inches

Body Length:

1.270 inches

Body Width:

0.635 inches

Body Height:

Between 0.890 inches and 0.930 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

Between 0.665 inches and 0.695 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

End Application:

Aircraft model f/a-18

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UNS

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0