

View Online at <https://aerobasegroup.com/nsn/5930-01-392-6331>

**Body Style:**

Surface mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Body Length:**

1.662 inches

**Body Width:**

1.270 inches

**Body Height:**

0.635 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.420 inches

**Actuator Height:**

1.140 inches

**Actuator Position-action Relationship:**

Left position momentary and right position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Integral

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes inductive dc and 4.000 amperes lamp dc and 15.000 amperes resistive dc and 10.000 amperes inductive ac and 2.000 amperes lamp ac and 15.000 amperes resistive ac

**Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 quick disconnect, female

**Specification Data:**

96906-ms27781-29f government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0