# NSN 5930-01-392-9306

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-392-9306

### Thread Class:

2a

Body Style:

Bushing mounted

# **Bushing Length:**

0.220 inches

# **Body Length:**

0.320 inches

### **Body Width:**

0.240 inches

#### **Body Height:**

0.340 inches

#### **Actuator Style:**

Round

#### **Actuator Diameter:**

0.100 inches

# Actuator Height:

lotaator noigi

0.155 inches

# Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

# Inclosure Type:

Hermetically sealed

# Mounting Method:

Threaded bushing

## Thready Qty Per Inch (tpi):

48

# Thread Size:

0.190 inches

#### Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive ac and 1.000 amperes resistive dc

#### **Precious Material And Location:**

Contact and terminal surfaces silver

#### **Thread Series Designator:**

Uns

# **Terminal Type And Quantity:**

2 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5930-01-392-9306

Push Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

