## NSN 5930-01-393-2514

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-393-2514 **Body Style:** Panel mounted **Body Width:** 0.8000 inches **Body Height:** 1.136 inches **Actuator Length:** 0.990 inches **Actuator Style:** Rectangular **Actuator Height:** 0.190 inches **Actuator Width:** 0.6000 inches **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 125.0 ac and 28.0 dc **Mounting Surface To Terminal End Distance:** 1.890 inches **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Nonpile-up Contact Arrangement:** 2 pole, double throw, both positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive ac and 8.000 amperes resistive dc **Test Data Document:** 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 6 tab, solder lug **Specification Data:** 81349-mil-s-22885/92 government specification Shelf Life: N/a **Unit Of Measure:** 

Fiig: A053a0

No

**Demilitarization:** 

## NSN 5930-01-393-2514

Push Switch - Page 2 of 2



Mil-std (military Standard):

Mil-prf-22885 spec.