## NSN 5930-01-393-7936

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-393-7936

| Body Style:  |
|--|
| Panel mounted  |
| Hazardous Locations/environmental Protection:  |
| Moisture proof   |
| Body Width:  |
| 0.870 inches   |
| Body Height:   |
| 0.870 inches   |
| Maximum Voltage Rating In Volts:   |
| 115.0 ac and 28.0 dc   |
| Mounting Surface To Terminal End Distance:   |
| 2.650 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Nonpile-up Contact Arrangement:  |
| 2 pole, double throw, one position momentary single switch unit  |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 2.000 amperes resistive ac and 1.000 amperes inductive ac and 0.750 amperes lamp ac and 2.000 amperes resistive dc and 1.000 amperes |
| inductive dc and 0.750 amperes lamp dc   |
| Terminal Type And Quantity:  |
| 17 tab, solder lug   |
| Specification Data:  |
| 49956-g528881-1 manufacturers source control   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A053a0   |