NSN 5930-01-394-7229

Lock Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-394-7229

Body Style:
Bushing mounted
Body Diameter:
0.687 inches
Bushing Length:
0.750 inches
Body Length:
1.960 inches
Maximum Voltage Rating In Volts:
115.00 ac and 28.00 dc
End Application:
An/ush-37 system by cage 00253
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Threaded bushing Contact Load Current Rating At Maximum Rated Voltage:
-
Contact Load Current Rating At Maximum Rated Voltage:
Contact Load Current Rating At Maximum Rated Voltage: 150.00 milliamperes resistive ac
Contact Load Current Rating At Maximum Rated Voltage: 150.00 milliamperes resistive ac Terminal Type And Quantity:
Contact Load Current Rating At Maximum Rated Voltage: 150.00 milliamperes resistive ac Terminal Type And Quantity: 8 solder stud
Contact Load Current Rating At Maximum Rated Voltage: 150.00 milliamperes resistive ac Terminal Type And Quantity: 8 solder stud Shelf Life:
Contact Load Current Rating At Maximum Rated Voltage: 150.00 milliamperes resistive ac Terminal Type And Quantity: 8 solder stud Shelf Life: N/a
Contact Load Current Rating At Maximum Rated Voltage: 150.00 milliamperes resistive ac Terminal Type And Quantity: 8 solder stud Shelf Life: N/a Unit Of Measure:
Contact Load Current Rating At Maximum Rated Voltage: 150.00 milliamperes resistive ac Terminal Type And Quantity: 8 solder stud Shelf Life: N/a Unit Of Measure:
Contact Load Current Rating At Maximum Rated Voltage: 150.00 milliamperes resistive ac Terminal Type And Quantity: 8 solder stud Shelf Life: N/a Unit Of Measure: Demilitarization:
Contact Load Current Rating At Maximum Rated Voltage: 150.00 milliamperes resistive ac Terminal Type And Quantity: 8 solder stud Shelf Life: N/a Unit Of Measure: Demilitarization: No