## NSN 5930-01-395-9111

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-395-9111

**Thread Class:** 

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

**Overall Length:** 

2.210 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.125 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.750 inches single actuator

**Overall Diameter:** 

Between 1.000 inches and 1.306 inches

**Nonturn Device Radius:** 

0.375 inches at 3: 00 o'clock

**Individual Section Quantity:** 

3

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

2 each section front

**Throw Quantity:** 

3 each section front

**Mounting Method:** 

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

2 each section

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

## NSN 5930-01-395-9111

Rotary Switch - Page 2 of 2

A052b0



Shaft Type:	
Round, flatted single actuator	
Terminal Type:	
Tab, solder lug	
Contact Switching Action:	
Breaks before makes each section rear	
Switch Actuator Positioning Increment:	
30.0 degrees single actuator	
Switch Actuator Stop Device Type:	
Fixed stop single actuator	
Contact Load Current Rating:	
2.0 amperes resistive load ac at sea level	
Style Designator:	
Tap, circular, bushing mount	
Test Data Document:	
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific	cation
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	iin
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unef single mounting facility	
Specification Data:	
81349-mil-s-3786/4 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	