

View Online at <https://aerobasegroup.com/nsn/5930-01-396-8625>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

0.510 inches

Body Width:

0.210 inches

Body Height:

0.350 inches

Actuator Style:

Undercut, pan head

Actuator Diameter:

0.062 inches

Actuator Height:

0.020 inches

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Switch Release Force:

7.5 grams

Switch Actuating Force:

10.0 centimeter-grams

Actuator Movement:

5.0 pretravel degrees

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 7.000 amperes resistive ac

Test Data Document:

81349-mil-prf-8805/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 turret

Specification Data:

81349-mil-prf-8805/4 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0

Mil-std (military Standard):

Mil-prf-8805 spec.