

View Online at <https://aerobasegroup.com/nsn/5930-01-396-8625>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.188 inches

**Body Length:**

0.510 inches

**Body Width:**

0.210 inches

**Body Height:**

0.350 inches

**Actuator Style:**

Undercut, pan head

**Actuator Diameter:**

0.062 inches

**Actuator Height:**

0.020 inches

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Switch Release Force:**

7.5 grams

**Switch Actuating Force:**

10.0 centimeter-grams

**Actuator Movement:**

5.0 pretravel degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 7.000 amperes resistive ac

**Test Data Document:**

81349-mil-prf-8805/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 turret

**Specification Data:**

81349-mil-prf-8805/4 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0

**Mil-std (military Standard):**

Mil-prf-8805 spec.