NSN 5930-01-399-7125



Thermostatic Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-399-7125 **Overall Length:** Between 1.160 inches and 1.260 inches **Overall Height:** 0.500 inches **Body Diameter:** 0.640 inches **Mounting Slot Width:** 0.140 inches **Body Height:** Between 0.375 inches and 0.460 inches **Unthreaded Mounting Hole Diameter:** 0.140 inches **Tempurature Sensing Element Type:** Internal sensor **Mounting Method:** Bracket and unthreaded hole and slot **Contact Action Stimulus:** Increase **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 500.0 milliamperes lamp load second voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 170.00 actuation point degrees fahrenheit and 155.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage Media For Which Designed: **Style Designator:** Disc w/flange Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0

NSN 5930-01-399-7125

Thermostatic Switch - Page 2 of 2



Mil-std (military Standard):

Mil-s-24236 spec.