

View Online at <https://aerobasegroup.com/nsn/5930-01-406-3873>

Body Style:

Bushing mount

Bushing Length:

0.469 inches

Body Length:

1.336 inches

Body Width:

0.734 inches

Body Height:

1.203 inches

Actuator Style:

Round

Actuator Diameter:

0.432 inches

Actuator Height:

0.921 inches

Actuator Position-action Relationship:

Center position maintained and down position momentary

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

End Application:

Weapon systems-wasp class lhd; whidbey island class lsd

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive ac and 25.000 amperes resistive dc

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 screw

Specification Data:

96906-ms24612 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0